



LOGISTIC

STABULON B - STABULON E ANTI-SLIP CORRUGATED TIE-SHEETS



COMPOSITION

- ▶ Anti-slip coating (top side)
- ▶ Corrugated board – B or E flute
- ▶ Anti-slip coating (bottom side)

QUALITY OF PRODUCT

- ▶ High non-slip properties
- ▶ Tear and puncture resistant to nails and damaged pallets
- ▶ Superior rigidity – high compression resistance
- ▶ **100% recyclable**
- ▶ ISO 14062 Eco-designed certified
- ▶ Tertiary packaging, indirect food contact

APPLICATION USE

- ▶ **Stabilize any packaging format**
- ▶ Manual and automated applications

PALLETIZATION

- ▶ Standard pallet sheet sizes. Custom sizes available.
- ▶ 330 sheets per skid – Stabulon B flute
- ▶ 500 sheets per skid – Stabulon E flute
- ▶ Available with cut corners

SPECIFICATION SHEET

Paper type	FSC recycled paper		Standards
Weight	400 g/sqm		ISO 536
Slide angle	Stabulon on Stabulon	Stabulon on Paper	NF Q 03-083
	≥ 50°	≥ 40°	
Static coefficient of friction	≥ 1,2	≥ 0,8	ISO 8295
Dynamic coefficient of friction	≥ 0,6	≥ 0,4	ISO 8295



TECHNICOAT
Solution

solution@cgp-coating.com - www.cgp-coating.com

